NOTICE

All drawings located at the end of the document.

CORRES CO			
DE ORDER #			
13 RF & 4.	<u> </u>	4	
DIST.	LTR	I ENC	17
rardini, Jacqueline	Х		August 6, 2003 K
AILSFORD, M.D.	<u> </u>		8
RRERA, D.W.	X.	<u> </u>	
RRI, M.S.	 		
LTON, J.C.	 	—	N. B' L LB'O L
COMINI, J.			Mr. Richard DiSalvo
RTINEZ, L.A.	 -	—	Environmental, Safety and Health
RKER. A.M.		—	•
WERS. K.	╁	 	Compliance and Restoration
OTT, G.K.		 	-
ELTON, D.C.	X		DOE, RFFO
EARS, M.S.	_		
ICE, K.D.			\
ORHEIS, G.M.			Mr. Steve Gunderson
TLER, J.L.	Х	X	Colorado Department of Public Health
			4300 Cherry Creek Drive South
DUSSARD, M	X		To the state of th



032-RF-01164

and Environment Denver, Colorado 80246-1530

Mr. Tim Rehder U.S. Environmental Protection Agency 999 18th Street, Suite 300 Denver, CO 80202-2466

TRANSMITTAL OF THE FINAL DATA SUMMARY REPORT (page replacements) FOR IHSS GROUP 900 - 4&5 - JLB-074-03

Enclosed are page replacements to be made to the FINAL DATA SUMMARY REPORT FOR IHSS GROUP 900 - 4&5. Please exchange former pages containing Tables 2 and 3 as well as Figure 2 (pages 5 through 24) with the new set as they have been modified to reflect a change in the radionuclide data. A new Table of Contents page has also been supplied. The document and NFAA recommendation was approved by CDPHE on July 23, 2003.

If you have any questions, please contact me at extension 5245.

REPLY TO RFP CC

JTHORIZED CLASSIFIER

SIGNATURE xemption - CEX-105-01

J. Lane Butler

Manager, Environmental Restoration Programs

TION ITEM STATUS

JLB:kg

PARTIAL/OPEN

CLOSED

sen 2603

CONTROL RECORD

ASSIFICATION:

CLASSIFIED NEIDENTIAL

Original and 1 cc – Richard DiSalvo

cc: Norma Castañeda

R APPROVALS:

Enclosures:

As stated

IIG & TYPIST INITIALS

Kaiser-Hill Company, L L C

Rocky Flats Environmental Technology Site, 10808 Hwy. 93 Unit B, Golden, CO 80403-8200 ● 303-966-7000

TABLE OF CONTENTS

1.0	Introduction	1
2.0	Site Characterization	1
3.0	Deviations From Planned Sampling Specifications	12
	Data Quality Assessment	
	4.1.1 Data Quality Assessment Process	13
	4.1.2 Verification and Validation of Results	14
	4.1.3 Accuracy	15
	4.1.4 Precision	20
	4.1.5 Completeness	22
	4.1.6 Sensitivity	23
	4.1.7 Summary of Data Quality	23
5.0	References	24
	LIST OF FIGURES	
Fion	ure 1 Location Map – PAC 900-175	2
	ure 2 Soil Results Greater Than Background Mean Plus Two Standard Deviations	
5"	Reporting/Detection Limits	
	1	
	LIST OF TABLES	
Tabl	ele 1 PAC 900-175 –Characterization Sampling Specifications	4
	ole 2 PAC 900-175 – Results Greater than Background Mean Plus Two Standard	
	Deviations or Reporting/Detection Limits	
Tabl	ole 3 PAC 900-175 Summary of Analytical Results	
	ole 4 PAC 900-175 - Deviations from Planned Sampling Specifications	
	ole 5 Laboratory Control Sample Evaluation	
	ole 6 Surrogate Recovery Summary	
Tab!	ole 7 Field Blank Summary	18
Tabl	ole 8 Sample Matrix Spike Evaluation	19
Tab!	ole 9 Sample Matrix Spike Duplicate Evaluation	20
Tab!	ole 10 Field Duplicate Sample Frequency	21
Tab!	ole 11 RPD Evaluation	21
Tab!	ble 12 Validation and Verification Summary	23
	APPENDIX	
App	pendix A IHSS Group 900-4&5 Wildlife Refuge Worker/Ecological Receptor	

Action Level Comparison Table

ENCLOSURE

Real and QC Data (compact disc)

Table 2
PAC 900-175 – Results Greater than Background Mean Plus Two Standard Deviations or Reporting/Detection Limits

Code	Analyte	Result	DL/RL Limit	Background Mean +2 SD	Wildlife Refuge Worker Action	Ecological Receptor Action	Unit
					Level	Level	
CK43-001	Antimony	3.90	0.42	•	409	1	mg/kg
CK43-002	Antimony	2.80	0.43	-	409	1	mg/kg
CL43-002	Antimony	0.92	0.44	t	409	ı	mg/kg
CK43-000	Benzo(a)anthracene	100.00	40.00	1	34900	800000	ug/kg
CK43-001	Benzo(a)anthracene	180.00	41.00	1	34900	800000	ug/kg
CK43-002	Benzo(a)anthracene	210.00	40.00	t	34900	800000	ug/kg
CL43-000	Benzo(a)anthracene	44.00	40.00	1	34900	800000	ug/kg
CL43-001	Benzo(a)anthracene	310.00	39.00	1	34900	800000	ug/kg
CL43-002	Benzo(a)anthracene	160.00	41.00	-	34900	800000	ug/kg
CK43-000	Benzo(a)pyrene	140.00	97.00	1	3490	25700	ug/kg
CK43-001	Benzo(a)pyrene	230.00	00.66	1	3490	25700	ug/kg
CK43-002	Benzo(a)pyrene	240.00	00'96		3490	25700	ug/kg
CL43-001	Benzo(a)pyrene	270.00	95.00	1	3490	25700	ug/kg
CL43-002	Benzo(a)pyrene	190.00	98.00	ŀ	3490	25700	ug/kg
CK43-000	Benzo(b)fluoranthene	130.00	100.00		34900	1010000	ug/kg
CK43-001	Benzo(b)fluoranthene	240.00	110.00	1	34900	1010000	ug/kg
CK43-002	Benzo(b)fluoranthene	230.00	100.00	•	34900	1010000	ug/kg
CL43-001	Benzo(b)fluoranthene	240.00	100.00	ı	34900	1010000	ug/kg
CL43-002	Benzo(b)fluoranthene	170.00	100.00	1	34900	1010000	ug/kg
CK43-000	Benzo(k)fluoranthene	150.00	00.96	-	349000	1010000	ug/kg
CK43-001	Benzo(k)fluoranthene	230.00	00.86	1	349000	1010000	ug/kg
CK43-002	Benzo(k)fluoranthene	240.00	95.00	1	349000	1010000	ug/kg
CL43-001	Benzo(k)fluoranthene	290.00	94.00	1	349000	1010000	ug/kg
CL43-002	Benzo(k)fluoranthene	200.00	97.00	•	349000	1010000	ug/kg
CK43-000	bis(2-Ethylhexyl)phthalate	82.00	71.00		1970000	•	ug/kg
CK43-001	bis(2-Ethylhexyl)phthalate	75.00	73.00		1970000	1	ug/kg

Table 2
PAC 900-175 – Results Greater than Background Mean Plus Two Standard Deviations or Reporting/Detection Limits

Code	Analyte	Result	DL/RL Limit	Background Mean +2 SD	Wildlife Refuge Worker Action Level	Ecological Receptor Action Level	Cuit
CK43-002	bis(2-Ethylhexyl)phthalate	310.00	70.00	1	1970000	1	ug/kg
CL43-000	bis(2-Ethylhexyl)phthalate	7400.00	70.00	3	1970000	1	ug/kg
CL43-001	bis(2-Ethylhexyl)phthalate	100.00	70.00	I	1970000	1	ug/kg
CL43-002	bis(2-Ethylhexyl)phthalate	170.00	72.00	1	1970000	1	ug/kg
CK43-000	Chrysene	150.00	55.00	1	3490000	,	ug/kg
CK43-001	Chrysene	260.00	56.00	1	3490000	1	ug/kg
CK43-002	Chrysene	260.00	54.00	ı	3490000	1	ug/kg
CL43-000	Chrysene	58.00	54.00		3490000	1	ug/kg
CL43-002	Chrysene	210.00	55.00	ŧ	3490000	ı	ug/kg
CK43-002	Dibenz(a,h)anthracene	64.00	48.00	ı	3490	ą	ug/kg
CK43-001	Dimethylphthalate	110.00	89.00	•	1000000000	1	ug/kg
CK43-002	Dimethylphthalate	320.00	86.00	ı	10000000000	ı	ug/kg
CK43-002	Di-n-butylphthalate	130.00	77.00	•	73700000	1	ug/kg
CK43-000	Fluoranthene	330.00	87.00	1	27200000	1	ug/kg
CL43-000	Fluoranthene	120.00	86.00	1	27200000	ı	ug/kg
CK43-000	Indeno(1,2,3-cd)pyrene	73.00	49.00	1	34900	£	ug/kg
CK43-001	Indeno(1,2,3-cd)pyrene	150.00	50.00	1	34900	1	ug/kg
CK43-002	Indeno(1,2,3-cd)pyrene	160.00	49.00	1	34900	ı	ug/kg
CL43-001	Indeno(1,2,3-cd)pyrene	150.00	49.00	ı	34900	1	ug/kg
CL43-002	Indeno(1,2,3-cd)pyrene	110.00	50.00	ı	34900		ug/kg
CL43-001	Lithium	11.60	0.24	11.55	20400	ŧ	mg/kg
CK43-000	Molybdenum	2.20	0.13	1	5110	ŀ	mg/kg
CK43-001	Molybdenum	1.10	0.13	1	\$110	ŀ	mg/kg
CK43-002	Molybdenum	2.40	0.13	ı	5110		mg/kg
CL43-000	Molybdenum	0.93	0.13	ı	5110	1	mg/kg
CL43-001	Molybdenum	2.40	0.13	ı	5110	1	mg/kg

Table 2
PAC 900-175 – Results Greater than Background Mean Plus Two Standard Deviations or Reporting/Detection Limits

		0				T	
Location	Analyte	Result	DL/RL	Background	Wildlife Refuge	Ecological	Unit
Code			Limit	Mean +2 SD	Worker Action Level	Receptor Action Level	
CL43-002	Molybdenum	0.74	0.13	1	5110	1	mg/kg
CK43-000	Nitrate	1.80	0.21	1	1000000	1	mg/kg
CK43-002	Nitrate	2.50	0.20	1	1000000	1	mg/kg
CL43-000	Nitrate	1.80	0.20	ı	1000000	ı	mg/kg
CL43-001	Nitrate	1.90	0.20	1	1000000		mg/kg
CL43-002	Nitrate	2.60	0.21	1	1000000		mg/kg
CK43-000	Nitrite	1.30	0.25	١	102000	-	mg/kg
CK43-001	Nitrite	1.40	0.25	1	102000	1	mg/kg
CL43-000	Nitrite	1.20	0.24	1	102000	١	mg/kg
CL43-001	Nitrite	1.20	0.24	1	102000		mg/kg
CL43-002	Nitrite	1.80	0.25	ı	102000	t	mg/kg
CK43-000	Pyrene	290.00	41.00	ı	22100000	1	ug/kg
CL43-000	Pyrene	100.00	82.00	1	22100000	ı	ug/kg
CL43-000	Pyrene	100.00	41.00	ı	22100000		ug/kg
CK43-000	Tin	2.00	0.29	ŝ	613000		mg/kg
CK43-001	Tin	1.60	0.28	t	613000	t	mg/kg
CK43-002	Tin	1.60	0.29	ı	613000		mg/kg
CL43-000	Tin	1.00	0.28	1	613000	\$	mg/kg
CL43-001	Tin	2.30	0.28	ı	613000	4	mg/kg
CL43-002	Tin	1.70	0.29	•	613000	•	mg/kg
CL43-000	Uranium-238	2.90	1.42	2.00	351	1600	pCi/g

DL/RL = Detection or Reporting Limit
— = Not Available
SD = Standard Deviation

Table 3
PAC 900-175 Summary of Analytical Results

		201	mmne e/T-00/	A AC 700-1/3 Summaly of Analytical Acsults	ennesw n				
Analyte	Total	Detection	Average		DL/RL	-	Wildlife	Ecological	Unit
	Number Samples Analyzed	Frequency	quency Concentration	Concentration		Mean Plus 2SD	Refuge Worker Action Level	Receptor Action Level	
1,2,4-Trichlorobenzene	7	0.00%	387.14	670	130		9230000		ug/kg
1,2-Dichlorobenzene	7	0.00%	387.14	670	130	1	31200000	,	ug/kg
1,4-Dichlorobenzene	7	0.00%	387.14	670	110	1	840000	•	ug/kg
2,4,5-Trichlorophenol	7	0.00%	387.14	029	150	1	102000000	1	ug/kg
2,4,6-Trichlorophenol	L	0.00%	387.14	029	100		3470000	,	ug/kg
2,4-Dichlorophenol	7	0.00%	387.14	670	180	1	3070000	ı	ug/kg
2,4-Dimethylphenol	7	0.00%	387.14	670	190	1	20400000	1	ug/kg
2,4-Dinitrophenol	7	0.00%	1871.43	3300	1000	1	2040000		ug/kg
2,4-Dinitrotoluene	7	0.00%	387.14	029	200	t	56300	1	ug/kg
2,6-Dinitrotoluene	7	0.00%	387.14	029	200	1	56300	1	ug/kg
2-Chloronaphthalene	7	0.00%	387.14	670	11	ı	81800000	1	ug/kg
2-Chlorophenol	7	0.00%	387.14	029	150	1	5110000	-	ug/kg
2-Methylnaphthalene	7	0.00%	387.14	029	120	1	20400000		ug/kg
2-Methylphenol	7	0.00%	387.14	029	160	1	36900000	1	ug/kg
2-Nitroaniline	7	0.00%	1871.43	3300	160	1	16700000	1	ug/kg
3,3'-Dichlorobenzidine	7	0.00%	1514.29	2600	140	ł	61300	1	ug/kg
4,6-Dinitro-2-methylphenol	7	0.00%	1871.43	3300	098	1	1020000		ug/kg
4-Chloroaniline	7	0.00%	387.14	029	96	1	2950000		ug/kg
4-Methylphenol	7	0.00%	387.14	670	150	1	3690000	•	ug/kg
4-Nitrophenol	7	0.00%	1871.43	3300	190	ı	8180000	,	ug/kg
Acenaphthene	7	0.00%	387.14	670	94	1	40800000	1	ug/kg
Aluminum	9	0.00%	11291.67	14600	1.9	16902	228000	ı	mg/kg
Americium-241	9	0.00%	1.06	1.23	1.23	0.02	92	1900	pCi/g
Anthracene	7	0.00%	387.14	. 029	160	•	204000000	+	ug/kg

Table 3
PAC 900-175 Summary of Analytical Results

Extended to the second of the									
Analyte		Detection	Average	Maximum	DL/KL	Backgound	Wildlife	Ecological	Cnit
	Number Samples Analyzed	Frequency	Concentration	Concentration		Mean Plus 2SD	Refuge Worker	Receptor Action	
Antimony	9	50.00%	1.48	3.9	0.44		409	,	mg/kg
Arsenic	9	0.00%	3.70	4.6	0.4	10.09	22.2	21.6	mg/kg
Barium	9	0.00%	82.88	95.7	0.055	141.26	26400		mg/kg
Benzo(a)anthracene	7	85.71%	239.14	670	79	1	34900	000008	ug/kg
Benzo(a)pyrene	7	71.43%	297.14	670	190	a	3490	25700	ug/kg
Benzo(b)fluoranthene	7	71.43%	288.57	670	200	1	34900	1010000	ug/kg
Benzo(k)fluoranthene	7	71.43%	302.86	670	190		349000	1010000	ug/kg
Benzoic Acid	7	0.00%	1871.43	3300	1200	1	10000000000	•	ug/kg
Benzyl Alcohol	7	0.00%	387.14	670	160	1	307000000		ug/kg
Beryllium	9	0.00%	0.38	0.46	0.052	0.97	921	2.15	mg/kg
bis(2-Chloroethyl)ether	7	0.00%	387.14	029	100	•	34800	ı	ug/kg
bis(2-Chloroisopropyl)ether	7	0.00%	387.14	670	140	1	547000	ı	ug/kg
bis(2-Ethylhexyl)phthalate	7	100.00%	2548.14	0026	140	1	1970000	ŧ	ug/kg
Butylbenzylphthalate	7	0.00%	387.14	670	69	-	147000000	•	ug/kg
Cadmium	9	0.00%	0.27	0.85	0.036	1.61	962	1	mg/kg
Calcium	9	50.00%	18968.33	47300	-	4467	ł	•	mg/kg
Chromium VI	9	100.00%	70.82	114	0.36	1	268	1	mg/kg
Chrysene	7	85.71%	285.43	670	110	-	3490000	1	ug/kg
Cobalt	9	0.00%	4.60	5.8	0.35	10.01	1550	ŧ	mg/kg
Copper	9	100.00%	37.00	74.4	0.19	18.06	40900	ı	mg/kg
Cs-137	9	0.00%	0.08	0.0987	0.0958	1.68	•	1	pCi/g
Di-n-butylphthalate	7	14.29%	357.14	670	150	1	73700000	1	ug/kg
Di-n-octylphthalate	7	0.00%	387.14	670	73	1	14700000	1	ug/kg
Dibenz(a,h)anthracene	7	14.29%	347.71	670	96	•	3490	1	ug/kg
Dibenzofuran	7	0.00%	387.14	029	170	ı	2950000	-	ug/kg

Ummary Report - IHSS Group 900-4&5

Table 3
PAC 900-175 Summary of Analytical Results

		FAC	FAC 200-1/5 Summary of Analytical Kesuits	ary of Anaiyuc	a Kesuits				
Analyte	Total Number Samples Analyzed	Detection Frequency	Average Concentration	Maximum Concentration	DLRL	Backgound Mean Plus 2SD	Wildlife Refuge Worker Action Level	Ecological Receptor Action Level	Unit
Diethylphthalate	7	0.00%	767.14	1300	110	ı	590000000	1	ug/kg
Dimethylphthalate	7	28.57%	350.00	029	170		10000000000		ug/kg
Fluoranthene	7	85.71%	477.14	069	170	,	27200000	•	ug/kg
Fluorene	7	0.00%	387.14	029	150	ł	40800000	1	ug/kg
Hexachlorobenzene	7	0.00%	387.14	670	150	,	17200	•	ug/kg
Hexachlorobutadiene	7	0.00%	387.14	670	200	3	147000	1	ug/kg
Hexachlorocyclopentadiene	7	%00.0	767.14	1300	29	ł	3500000	1	ug/kg
Hexachloroethane	7	0.00%	387.14	029	100	1	737000	1990000	ug/kg
Indeno(1,2,3-cd)pyrene	7	71.43%	236.14	670	86	,	34900	•	ug/kg
Iron	9	16.67%	15600.00	18900	1.7	18037	307000	1	mg/kg
Isophorone	7	0.00%	387.14	670	140		29100000	f	ug/kg
Lead	9	%29.99	26.63	40.2	0.21	54.62	1000	25.6	mg/kg
Lithium	9	16.67%	10.22	11.6	0.25	11.55	20400	-	mg/kg
Manganese	9	0.00%	184.50	269	0.043	365.08	3480	9	mg/kg
Mercury	9	0.00%	0.02	0.036	0.0012	0.13	25200	1	mg/kg
Molybdenum	9	100.00%	1.63	2.4	0.13	ı	5110	1	mg/kg
n-Nitrosodiphenylamine	7	0.00%	387.14	029	150	1	7810000	ŧ	ug/kg
n-Nitrosodipropylamine	7	0.00%	387.14	029	180	ı	5470	1	ug/kg
Naphthalene	7	0.00%	387.14	0.29	140	1	3090000	1	ug/kg
Nickel	9	100.00%	46.90	69.7	0.45	14.91	20400	ſ	mg/kg
Nitrate	9	100.00%	3.62	11.1	0.21	1	1000000	I	mg/kg
Nitrite	9	83.33%	2.00	5.1	0.25	ſ	102000	1	mg/kg
Nitrobenzene	7	%00.0	387.14	670	170	ſ	332000	\$	ug/kg
Pentachlorophenol	7	0.00%	1871.43	3300	750	-	162000	•	ug/kg
Phenol	7	0.00%	387.14	029	140	1	613000000	١	ug/kg
			The state of the s						1

PAC 900-175 Summary of Analytical Results Table 3

				,					
Analyte	Total Dete Number Freq Samples Analyzed	Detection Frequency	ection Average Maximum uency Concentration	Maximum Concentration	DLRL	DL/RL Backgound Mean Plus 2SD	Wildlife Refuge Worker Action Level	Ecological Receptor Action Level	Unit
Plutonium-239/240	9	%00'0	11.81	13.1784	1.23	0.07	50	3800	pCi/g
Pyrene	7	100.00%	371.43	069	82	1	22100000		ug/kg
Selenium	6	0.00%	0.46	99.0	0.42	1.22	5110	1	mg/kg
Silver	6	0.00%	0.07	290.0	0.067	1	5110		mg/kg
Strontium	9	16.67%	30.12	51.4	0.016	48.94	613000	1	mg/kg
Tin	6	100.00%	1.70	2.3	0.29	1	613000		mg/kg
Uranium-235	9	0.00%	0.13	0.224	0.224	60.0	8	1900	pCi/g
Uranium-238	9	16.67%	1.53	2.9	1.64	2.00	351	0091	pCi/g
Vanadium	9	0.00%	27.03	30.4	0.31	45.59	7150	433	mg/kg
Zinc	9	83.33%	111.12	172	0.59	73.76	307000	1	mg/kg

DL/RL = Detection or Reporting Limit
- = Not Available
SD = Standard Deviation

3.0 DEVIATIONS FROM PLANNED SAMPLING SPECIFICATIONS

Deviations from the planned sampling specifications described in IASAP Addendum #IA-02-02 (DOE 2002a) are presented in the following table.

Table 4
PAC 900-175 - Deviations from Planned Sampling Specifications

Sampling Location Code	Planned Easting	Planned Northing	Actual Easting	Actual Northing	Comments
CL43-0002	2084965.91	750060.59	2084985.46	750090.89	All sample location deviations
CK43-0002	2084929.95	750062.37	2084894.08	750064.21	resulted from utilities,
CL43-0001	2084985.43	750090.83	2084949.48	750092.62	structures, or auger refusal.
CL43-0000	2084949.48	750092.62	2084913.24	750078.42	
CK43-0000	2084913.52	750094.40	2084949.95	750075.39	,

4.0 DATA QUALITY ASSESSMENT

The Data Quality Objectives (DQOs) for this project, as defined in the IASAP (DOE 2001), were achieved based on the Data Quality Assessment (DQA) provided in the following sections. The DQO/DQA process ensures that the type, quantity, and quality of environmental data used in decision making are defensible, with emphasis on attaining adequate (statistical) confidence in the decisions. The DQO/DQA process is based on the following guidance and requirements:

- EPA QA/G-4, 1994a, Guidance for the Data Quality Objective Process;
- EPA QA/G-9, 1998, Guidance for the Data Quality Assessment Process; Practical Methods for Data Analysis; and
- DOE Order 414.1A, 1999, Quality Assurance.

4.1.1 Data Quality Assessment Process

The DQA process ensures the type, quantity, and quality of environmental data used in decision making are defensible. Results are compared to method requirements and project goals. The results of these comparisons are summarized for RFCA COCs where the result could impact project decisions. Particular attention is paid to those values near ALs when quality control (QC) results could indicate unacceptable levels of uncertainty for decision-making purposes. The DQA process is based on the following guidance and requirements:

- EPA QA/G-4, 1994a, Guidance for the Data Quality Objective Process;
- EPA QA/G-9, 1998, Guidance for the Data Quality Assessment Process; Practical Methods for Data Analysis; and
- DOE Order 414.1A, 1999, Quality Assurance.

Verification and validation (V&V) of the data are the primary components of the DQA. The final data are compared with original project DQOs and evaluated with respect to project decisions; uncertainty within the decisions; and quality criteria required for the data, specifically precision, accuracy, representativeness, completeness, comparability, and sensitivity (PARCCS). Validation criteria are consistent with the following RFETS-specific documents and industry guidelines:

- EPA 540/R-94/012, 1994b, USEPA Contract Laboratory Program National Functional Guidelines for Organic Data Review;
- EPA 540/R-94/013, 1994c, USEPA Contract Laboratory Program National Functional Guidelines for Inorganic Data Review; and
- Kaiser-Hill Company, L.L.C.(K-H) V&V Guidelines:



13

- General Guidelines for Data Verification and Validation, DA-GR01-v2, 2002a.
- V&V Guidelines for Isotopic Determinations by Alpha Spectrometry, DA-RC01-v2, 2002b.
- V&V Guidelines for Volatile Organics, DA-SS01-v3, 2002c.
- V&V Guidelines for Semivolatile Organics, DA-SS02-v3, 2002d.
- V&V Guidelines for Metals, DA-SS05-v3, 2002e.
- Lockheed-Martin, 1997, Evaluation of Radiochemical Data Usability, ES/ER/MS-5.

This report will be submitted to the Comprehensive Environmental, Response, Compensation and Liability Act (CERCLA) Administrative Record (AR) for permanent storage 30 days after being provided to the Colorado Department of Public Health and Environmental (CDPHE) and/or the U.S. Environmental Protection Agency (EPA).

4.1.2 Verification and Validation of Results

Verification ensures that data produced and used by the project are documented and traceable in accordance with quality requirements. Validation consists of a technical review of all data that directly support the project decisions so that any limitations of the data relative to project goals are delineated and the associated data are qualified accordingly. The V&V process defines the criteria that constitute data quality, namely PARCCS parameters. Data traceability and archival are also addressed. V&V criteria include the following:

- Chain-of-custody;
- Preservation and hold-times;
- Instrument calibrations;
- Preparation blanks;
- Interference check samples (metals);
- Matrix spikes/matrix spike duplicates (MS/MSD);
- Laboratory control samples (LCS);
- Field duplicate measurements;
- Chemical yield (radiochemistry);
- Required quantitation limits/minimum detectable activities (sensitivity of chemical and radiochemical measurements, respectively); and
- Sample analysis and preparation methods.

Evaluation of V&V criteria ensures that PARCCS parameters are satisfactory (i.e., within tolerances acceptable to the project). Satisfactory V&V of laboratory quality controls are

captured through application of validation "flags" or qualifiers to individual records. Validation results are summarized in the "Completeness" subsection.

Field sampling was conducted according to the approved IASAP, including related SOPs and addenda. Raw hardcopy data (e.g., individual analytical data packages) are currently filed by RIN and are maintained by Kaiser-Hill Analytical Services Division (K-H ASD); older hardcopies may reside in the Federal Center in Lakewood, Colorado. Electronic data are stored in the RFETS Soil and Water Database (SWD).

Both real and QC data, as of June 11, 2003 are included on the enclosed compact disc (CD).

4.1.3 Accuracy

The following measures of accuracy were evaluated:

- Laboratory Control Sample Evaluation;
- Surrogate Evaluation;
- Field Blanks; and
- Sample Matrix Spike Evaluation.

Laboratory Control Sample Evaluation

The frequency of LCS measurements, relative to each laboratory batch, is given in Table 5. LCS frequency was adequate based on at least one LCS per batch. The minimum and maximum LCS results are also tabulated, by chemical, for the project. While not all LCS results are within tolerances, project decisions based on AL exceedances were not affected. Any qualifications of results due to LCS performance exceeding upper or lower tolerance limits are captured in the V&V flags, described in the Completeness Section.



	Test Method	SW-846 8270B	SW-846 8270B	SW-846 8270B	SW-846 8270B	SW-846 6010/6010B	SW9056 OR E300.0 PREP E300.0	SW9056 OR E300.0 PREP E300.0	SW-846 8270B	SW-846 8270B														
	Unit	%REC	%REC	%REC	%REC	%REC SW	%REC SV	%REC SV	%REC	%REC														
	Number of Laboratory Batches	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	p	2	2	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	2	2	2
Table 5 Laboratory Control Sample Evaluation	Number of Laboratory Samples	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	_	2	2	2	2	2	2
Table 5 trol Sample	Minimum Maximum	92	85	73	74	94	06	92	95	06	93	06	91	100	93	100	93	- 93	06	93	95	96	72	73
T atory Conti	Minimum	89	75	70	69	92	88	913	93	06	91	88	06	65	06	<u>56</u> .	91	93	87	16	94	96	70	89
Labor	Result Type	271	CC	277	27	27	27	27	TC	TC	TC	rc	CC	27	27	CC	CC	rc	CC	CC	CC	ρη	TC	CC
	Analyte	1,2,4-TRICHLOROBENZENE	2,4-DINITROTOLUENE	2-CHLOROPHENOL	ACENAPHTHENE	ALUMINUM	ANTIMONY	ARSENIC	BARIUM	BERYLLIUM	CADMIUM	COBALT	COPPER	IRON	LEAD	ГІТНІОМ	MANGANESE	MERCURY	MOLYBDENUM	NICKEL	NITRATE AS N	NITRITE AS N	N-NITROSO-DI-N- PROPYLAMINE	P-DICHLOROBENZENE
	CAS Number	120-82-1	121-14-2	95-57-8	83-32-9	7429-90-5	7440-36-0	7440-38-2	7440-39-3	7440-41-7	7440-43-9	7440-48-4	7440-50-8	7439-89-6	7439-92-1	7439-93-2	7439-96-5	7439-97-6	7439-98-7	7440-02-0	14797-55-8	14797-65-0	621-64-7	106-46-7

Table 5
Laboratory Control Sample Evaluation

CAS	Analyte	Result	Minimum		Maximum Number of	Number of	Unit	Test Method
Number		Type			Laboratory Samples	Laboratory Laboratory Samples Batches		
87-86-5	PENTACHLOROPHENOL	271	99	70	2	2	%REC	SW-846 8270B
108-95-2	PHENOL	Ω	70	75	2	2	%REC	SW-846 8270B
100-02-7	P-NITROPHENOL	27	62	99	2	7	%REC	SW-846 8270B
129-00-0 PYRENE	PYRENE	271	63	72	2	2	%REC	SW-846 8270B
7782-49-2	7782-49-2 SELENIUM	27	68	93	2	2	%REC	SW-846 6010/6010B
7440-22-4 SILVER	SILVER	271	92	93	2	C	%REC	SW-846 6010/6010B
7440-24-6	7440-24-6 STRONTIUM	27	92	94	2	2	%REC	SW-846 6010/6010B
7440-31-5 TIN	TIN	CC	88	68	2	ĩ	%REC	SW-846 6010/6010B
7440-62-2	7440-62-2 VANADIUM	CC	06	16	2	2	%REC	SW-846 6010/6010B
7440-66-6 ZINC	ZINC	27	06	95	2	2	%REC	SW-846 6010/6010B

Surrogate Recovery Summary Table 6

	Camining Case Series	6		
VOC Surrogate Recoveries	veries			
Number of Samples	Analyte	Minimum	Maximum	Unit Code
2	1,2-DICHLOROETHANE-D4	06	94	%REC
2	4-BROMOFLUOROBENZENE	94	95	%REC
2	TOLUENE-D8	95	95	%REC
SVOC Surrogate Recoveries	overies			
Number of Samples	Analyte	Minimum	Maximum	Unit Code
12	TERPHENYL-D14	69	88	%REC
12	2-FLUOROBIPHENYL	65	83	%REC
12	2-FLUOROPHENOL	09	62	%REC
12	NITROBENZENE-D5	59	6L	%REC

Surrogate Evaluation

The frequency of surrogate measurements, relative to each laboratory batch, is given in Table 6. Surrogate frequency was adequate based on at least one set per sample. The minimum and maximum surrogate results are tabulated by chemical for the entire project. Any qualifications of results due to surrogate results are captured in the V&V flags, described in the Completeness Section.

Field Blank Evaluation

Results of the field blank analyses are listed in Table 7. Detectable amounts of contaminants within field or laboratory blanks could indicate cross-contamination of samples. However, none of the chemicals detected in laboratory blanks were detected in real samples with concentrations exceeding ALs; therefore, no significant laboratory blank contamination is indicated. Field blanks were not collected for this project. Consequently, all detectable concentrations of arsenic and lead are considered present at the sampling locations, and not due to cross-contamination.

Table 7
Field Blank Summary

Sample QC Code	Test Method Name	Analyte	Maximum Detected Value	Unit
RB	GAMMA	Uranium-235	0.2	pCi/g
RB	GAMMA	Uranium-238	4	pCi/g
FB	SW8260B	Toluene	2	ug/L
RB	SW8260B	Toluene	0.3	ug/L
FB	SW8260B	2-Butanone	, 4	ug/L
FB	SW8260B	Naphthalene	0.8	ug/L
eld Blanks (Trip, Rinse	e, Field) results greater than	n detection limits	(not *U* Qualified)	

Sample Matrix Spike Evaluation

The frequency of MS measurements, relative to each laboratory batch, was adequate based on at least one MS per batch. The minimum and maximum of MS results are summarized by chemical, for the entire project in Table 8. Although low recovery values may indicate negative bias for some analytes, recovery values alone do not result in rejection of results. Qualification of results because of out of tolerance spike recoveries is noted by electronic flagging of the results.

Table 8

		Sam	ple Matrix	Spike Eva	luation			
CAS Number	Analyte	Result Type	Minimum	Maximum	Number of Laboratory Samples		Unit	Test Method
120-82-1	1,2,4-TRICHLOROBENZENE	MS	62	68	2	2	%REC	SW-846 8270B
121-14-2	2,4-DINITROTOLUENE	MS	70	85	2	2	%REC	SW-846 8270B
95-57-8	2-CHLOROPHENOL	MS	64	70	2	2	%REC	SW-846 8270B
83-32-9	ACENAPHTHENE -	MS	64	75	2	2	%REC	SW-846-8270B
7429-90-5	ALUMINUM	MS	98	314	3	3	%REC	SW-846 6010/6010B
7440-36-0	ANTIMONY	MS	35	97	3	3	%REC	SW-846 6010/6010B
7440-38-2	ARSENIC	MS	91	97	3	3	%REC	SW-846 6010/6010B
7440-39-3	BARIUM	MS	102	103	3	3	%REC	SW-846 6010/6010B
7440-41-7	BERYLLIUM	MS	91	97	3	3	%REC	SW-846 6010/6010B
7440-43-9	CADMIUM	MS	90	100	3	3	%REC	SW-846 6010/6010B
7440-48-4	COBALT	MS	88	97	3	3	%REC	7440-48-4
7440-50-8	COPPER	MS	97	108	3	3	%REC	7440-50-8
7439-89-6	IRON	MS	102	672	3	3	%REC	7439-89-6
7439-92-1	LEAD	MS	94	99	3	3	%REC	7439-92-1
7439-93-2	LITHIUM	MS	100	105	3	3	%REC	7439-93-2
7439-96-5	MANGANESE	MS	98	100	3	3	%REC	7439-96-5
7439-97-6	MERCURY	MS	48	48	1	1	%REC	7439-97-6
7439-98-7	MOLYBDENUM	MS	83	98	3	3	%REC	7439-98-7
7440-02-0	NICKEL	MS	98	117	3	3	%REC	7440-02-0
14797-55-8	NITRATE AS N	MS	94	94	1	1	%REC	14797-55-8
14797-55-8	NITRATE AS N	MS	89 ·	89	1	1	%REC	14797-55-8
14797-65-0	NITRITE AS N	MS	100	100	1	1	%REC	14797-65-0
14797-65-0	NITRITE AS N	MS	91	91	1	1	%REC	14797-65-0
621-64-7	N-NITROSO-DI-N- PROPYLAMINE	MS	63	67	2	2	%REC	621-64-7
106-46-7	P-DICHLOROBENZENE	MS	60	65	2	2	%REC	106-46-7
87-86-5	PENTACHLOROPHENOL	MS	52	52	2	2	%REC	87-86-5
108-95-2	PHENOL	MS	64	71	2	2	%REC	108-95-2
100-02-7	P-NITROPHENOL	MS	60	61	2	2	%REC	100-02-7
129-00-0	PYRENE	MS	65	76	2	2	%REC	129-00-0
7782-49-2	SELENIUM	MS	90	96	3	3	%REC	7782-49-2
7440-22-4	SILVER	MS	90	102	3	3	%REC	7440-22-4
7440-24-6	STRONTIUM	MS	99	101	3	3	%REC	7440-24-6
7440-31-5	TIN	MS	85	97	3	3	%REC	7440-31-5
7440-62-2	VANADIUM	MS	100	121	3	3	%REC	7440-62-2
7440-66-6	ZINC	MS	78	98	3	3	%REC	7440-66-6




4.1.4 Precision

Matrix Spike Duplicate Evaluation

Laboratory precision is measured through use of MSD. Adequate frequency of MSD measurements is indicated by at least one MSD in each laboratory batch. Although some RPD values, listed in Table 9, exceed the maximum target of 35 percent, all sample results were repeatable at concentrations well below their respective ALs.

Table 9
Sample Matrix Spike Duplicate Evaluation

Analyte Name	Number of	Number of	Max RPD
	Sample Pairs		(percent)
1,2,4-TRICHLOROBENZENE	2	2	8
2,4-DINITROTOLUENE	2	2	8
2-CHLOROPHENOL	2	2	8
ACENAPHTHENE	2	2	5
ALUMINUM	3	3	3
ANTIMONY	3	3	1
ARSENIC	3	3	7
BARIUM	3	3	9
BERYLLIUM	3	3	6
CADMIUM	3	3	6
CADMIUM	3	3	6
COBALT	3	3	7
COPPER	3	3	25
IRON	3	3	98
LEAD	3	3	121
LITHIUM	3	- 3	7
MANGANESE	3	3	43
MERCURY	1	1	33
MOLYBDENUM	3	3	6
NICKEL	3	3	75
NITRATE AS N	1	1	1
NITRATE AS N	1	1	5
NITRITE AS N	1	1	1
NITRITE AS N	1	1	4
N-NITROSO-DI-N-PROPYLAMINE	2	2	9
P-DICHLOROBENZENE	2	2	7
PENTACHLOROPHENOL	2	2	7
PHENOL	2	2	11
P-NITROPHENOL	2	2	5
PYRENE	2	2	3
SELENIUM	3	3	5
SILVER	3	3	7
STRONTIUM	3	3	11
TIN	3	3	6
VANADIUM	3	3	10
ZINC	3	3	12



Field duplicate results reflect sampling precision or overall repeatability of the sampling process. The frequency of field duplicate collection should exceed 1 field duplicate per 20 real samples, or 5 percent. Data in Table 10 indicates that duplicate sampling frequencies were adequate for all suites except radionuclides.

A common metric for evaluating precision is the relative percent difference (RPD) value; RPD values are given in Table 11. Ideally, RPDs of less than 35 percent (in soil) indicate satisfactory precision. If contaminant concentrations exceeded ALs and the 35% RPD value, then associated results were reviewed to determine if the magnitude of imprecision could impact decisions (i.e., could sample concentrations measured below ALs exceed AL?).

Table 10 Field Duplicate Sample Frequency

Test Method Name	Sample Code	Number of Samples	Percent of Duplicate Samples
GAMMA SPECTROSCOPY	REAL	6	0
SW-846 6010/6010B	REAL	6	17
SW-846 6010/6010B	DUP	1	7
SW-846 8270B	REAL	6	17
SW-846 8270B	DUP	1	7
SW9056 OR E300.0 PREP E300.0	REAL	6	17
SW9056 OR E300.0 PREP E300.0	DUP	1	

Table 11 RPD Evaluation

Analyte	Max of RPD (percent)
1,2,4-TRICHLOROBENZENE	0
2,4,5-TRICHLOROPHENOL	0
2,4,6-TRICHLOROPHENOL	0
2,4-DICHLOROPHENOL	0
2,4-DIMETHYLPHENOL	0
2,4-DINITROPHENOL	0
2,4-DINITROTOLUENE	0
2,6-DINITROTOLUENE	0
2-CHLORONAPHTHALENE	0
2-CHLOROPHENOL	0
2-NITROANILINE	0
4-CHLOROANILINE	0
ACENAPHTHENE	0 .
ALUMINUM	2
ANTHRACENE	0
ANTIMONY	26
ARSENIC	8
BARIUM	5
BENZO(A)ANTHRACENE	37
BENZO(A)PYRENE	24
BENZO(B)FLUORANTHENE	19
BENZO(K)FLUORANTHENE	42



Table 11 RPD Evaluation

Analyte	Max of RPD
- Annual Co	(percent)
BENZOIC ACID	0
BERYLLIUM	29
BIS(2-ETHYLHEXYL)PHTHALATE	162
BUTYLBENZYLPHTHALATE	0
CHRYSENE	33
COBALT	2
COPPER	49
DIBENZ(A,H)ANTHRACENE	0
DIBENZOFURAN	0
FLUORANTHENE	29
FLUORENE	0
HEXACHLOROBENZENE	0
HEXACHLOROBUTADIENE	0
HEXACHLOROCYCLOPENTADIENE	1
HEXACHLOROETHANE	0
INDENO(1,2,3-CD)PYRENE	20
IRON	17
ISOPHORONE	0
LEAD	57
LITHIUM	6
MANGANESE	4
MERCURY	30
MOLYBDENUM	108
NAPHTHALENE	0
NICKEL	3
NITROBENZENE	0
N-NITROSODIPHENYLAMINE	0
PENTACHLOROPHENOL	0
PHENOL	0
PYRENE	37
SELENIUM	2
SILVER	0
STRONTIUM	21
TIN	34
VANADIUM	3
ZINC	2

4.1.5 Completeness

Based on original project DQOs, a minimum of 25 percent of ER Program analytical (and radiological) results must be formally verified and validated. Of that percentage, no more than 10 percent of the results may be rejected, which ensures that analytical laboratory practices are consistent with quality requirements. Table 12 shows the number and percentage of validated records (codes without "1"), the number and percentage of verified records (codes with "1"), and the percentage of rejected records for each analyte group. The frequency of validation is within

project quality requirements for all suites except radionuclides. A check of hardcopy V&V records indicates that validation frequency is better than the minimum of 25 percent for both alpha and gamma spectroscopy, but the associated validation flags have not yet been uploaded to electronic records in the Soil Water Database (SWD). Following upload of the V&V flags to SWD, the validation frequency of electronic records will be acceptable.

The frequency of validation is in compliance with the RFETS validation goal of 25 percent of all analytical records indicating that these data are adequate.

Table 12
Validation and Verification Summary

Validation Code	Number of Records	Radionuclides	Metals	Inorganics
V&V	185	119	0	0
J	81	0	81	0
V	514	0 -	105	12
Total	780	119	186	12
Total Validated	595	0	186	12
Percent Validated	76%	0%	100%	100%
Total Verified	0%	0%	0%	0%
Percent Verified	0%	0%	0%	0%
Percent Rejected	0%	0%	0%	0%

KEY:

1, V1 - Verified

J, J1 - Estimated

UJ1 - Estimated detection limit

V - Validated

4.1.6 Sensitivity

Reporting limits, in units of ug/kg for organics, mg/kg for metals, and pCi/g for radionuclides, were compared with RFCA WRW and Ecological Receptor ALs. Adequate sensitivities of analytical methods were attained for all COCs that affect project decisions. "Adequate" sensitivity is defined as a reporting limit less than an analyte's associated AL, typically less than one-half the AL.

4.1.7 Summary of Data Quality

The RPDs greater than 35 percent indicate that the sampling precision limits of some analytes have been exceeded. However, the imprecision does not affect project decisions because with the exception of lead exceeding the Ecological Receptor AL but below background, there were no AL exceedances and no records were rejected. Compliance with the project quality requirements and RFETS validation goal of 25 percent of all analytical records indicates that these data are adequate. If additional V&V information is received, IHSS Group 900-4&5 records will be updated in SWD. Data qualified as a result of additional data will be assessed as part of the Comprehensive Risk Assessment process.

Data collected and used for IHSS Group 900-4&5 are adequate for decision-making.



5.0 REFERENCES

DOE, 1992-2001, Historical Release Reports for the Rocky Flats Plant, Rocky Flats Plant, Golden, Colorado.

DOE, 1999, Order 414.1A, Quality Assurance.

DOE, 2000, Rocky Flats Cleanup Agreement (RFCA), Attachment 5, March.

DOE, 2001, Industrial Area Sampling and Analysis Plan, Rocky Flats Environmental Technology Site, Golden, Colorado, June.

DOE, 2002á, Industrial Area Sampling and Analysis Plan Addendum #IA-02-02, Rocky Flats Environmental Technology Site, Golden, Colorado, January.

DOE, 2002b, Environmental Restoration RFCA Standard Operating Protocol for Routine Soil Remediation, Rocky Flats Environmental Technology Site, Golden, Colorado, January.

EPA QA/G-4, 1994a, Guidance for the Data Quality Objective Process.

EPA 540/R-94/012, 1994b, USEPA Contract Laboratory Program National Functional Guidelines for Organic Data Review.

EPA 540/R-94/013, 1994c, USEPA Contract Laboratory Program National Functional Guidelines for Inorganic Data Review.

EPA QA/G-9, 1998, Guidance for the Data Quality Assessment Process; Practical Methods for Data Analysis.

Kaiser-Hill (K-H), 2002a, General Guidelines for Data Verification and Validation, DA-GR01-v2, October.

K-H, 2002b, V&V Guidelines for Isotopic Determinations by Alpha Spectrometry, DA-RC01-v2, October.


K-H, 2002c, V&V Guidelines for Volatile Organics, DA-SS01-v3, October.

K-H, 2002d, V&V Guidelines for Semivolatile Organics, DA-SS02-v3, October.

K-H, 2003e, V&V Guidelines for Metals, DA-SS05-v3, October.

Lockheed-Martin, 1997, Evaluation of Radiochemical Data Usability, ES/ER/MS-5.





Best Available Copy

(1)